




















DOWNLIGHTS ÖVERSIKT

Downlightsfamilj		Effekt (W)	Spridning	Armaturlumen	Håltagning (mm)	Färgtemperatur	Styrning	Don ingår	IP-klass
	R84	8	36°/ 60°	550lm	82-90	2700K, 3000K, Dim to warm	Dim, DALI	Ja	IP54
	R84 SC	8	40°	650lm	83-90	3000K	Dim	Ja	IP44
	R74	6	36°	400lm	70-74	2700K, 3000K	Dim	Ja	IP54
	R42	3	60°	270lm	42-45	2700K, 3000K	Dim	Ja	IP54
	R25	1,5	36°	90lm	25	2700K, 3000K	Dim	Ja ej dimbart	IP54
	WLD Reko I	7	36°	730lm	89x89	2700K, 3000K	Dim, DALI	Ja	IP54
	WLD Reko II	2x7	36°	2x730lm	89x169	2700K, 3000K	Dim, DALI	Ja	IP54
	WLD Reko III	3x7	36°	2x730lm	89x249	2700K, 3000K	Dim, DALI	Ja	IP54
	WLD R8	8	60°	640lm	90-100	3000K, 4000K	DALI	Ja	IP44
	WLD R20	20	60°	2200lm	160-170	3000K, 4000K	DALI	Ja	IP44
	WLD R30	30	60°	3300lm	200-210	3000K, 4000K	DALI	Ja	IP44
	WLD-S84	8	110°	600lm	84-95	3000K	Dim	Ja	IP54
	WLD-S	20	80°	1190lm	220-230	3000K	DALI	Ja inbyggt	IP20
	WLD-Pir	8	120°	690lm	83-95	3000K	PIR	Ja	IP54
	WLD FR70	8	60°	800lm	70-74	2700K,3000K,4000K	Dim	Ja	IP65
	WLD FR72	7	60°	650lm	72-80	2700K,3000K,4000K	Dim	Ja inbyggt	IP65
	WLD GU10 fast	5	60°	380lm	68-74	3000K	Dim	Ja	IP65
	WLD GU10 tilt	5	60°	380lm	73-78	3000K	Dim	Ja	IP23
	M64	4	40°	300lm	60-64	3000K	Dim	Ja	IP44